


Details



Side A

- 1 *Plug*
- Type: Type M (SANS 164-1)
 - Contacts: L (Life)
E (Earth)
N (Neutral)
 - Gender: Male
- 2 *Housing*
- Material: PVC, Molded
 - Orientation: Angled (90°)
 - Color: Black
- 3 *Ratings*
- Current: 16A (max.)
 - Voltage: 250V (max.)

Wire

- 1 *Conductors*
- Type: H05VV-F 3x 0.75mm²
 - Wires: Brown (L = Life)
Yellow/Green (E = Earth)
Blue(N = Neutral)
- 2 *Jacket*
- Material: PVC
 - Color: Black

Side B

- 1 *Connector*
- Type: C13 (IEC 60320-1)
 - Contacts: L (Life)
E (Earth)
N (Neutral)
 - Gender: Female
- 2 *Housing*
- Material: PVC, Molded
 - Orientation: Straight (180°)
 - Color: Black
- 3 *Ratings*
- Current: 10A (max.)
 - Voltage: 250V (max.)

Wiring diagram

Side A	Side B	Color
L	L	Brown
E	E	Yellow/Green
N	N	Blue

Approvals



Part number Description

S12A-027-01007 Power Cord, South Africa - C13, 3x 0.75mm², Black, 1.8m

Image

