


Details



Side A

- 1 *Plug*
 - Type: Type M (SANS 164-1)
 - Contacts: L (Life)
N (Neutral)
 - Gender: Male
- 2 *Housing*
 - Material: PVC, Molded
 - Orientation: Angled (90°)
 - Color: Black
- 3 *Ratings*
 - Current: 10A (max.)
 - Voltage: 250V (max.)

Wire

- 1 *Conductors*
 - Type: H03VVH2-F 2x 0.75mm²
 - Wires: Brown (L = Life)
Blue(N = Neutral)
- 2 *Jacket*
 - Material: PVC
 - Color: Black

Side B

- 1 *Connector*
 - Type: C7 (IEC 60320-1)
 - Contacts: N (Neutral)
L (Life)
 - Gender: Female
- 2 *Housing*
 - Material: PVC, Molded
 - Orientation: Straight (180°)
 - Color: Black
- 3 *Ratings*
 - Current: 2.5A (max.)
 - Voltage: 250V (max.)

Wiring diagram

	Side A	Side B	Color
N	_____	N	Blue
L	_____	L	Brown

Approvals



Part number Description

S12A-027-33007	Power Cord, South Africa - C7, 2x 0.75mm², Black, 1.8m
S12A-027-33008	Power Cord, South Africa - C7, 2x 0.75mm², Black, 2.5m

Image

